



Harvey Thatch

INSTALLATION SPECIFICATION FOR RE-ROOFING AND NEW ROOFS

Note:

- A) In order to comply to the A-Class Fire rating as tested in accordance to SANS 1077 - part 12 (CSIR), Harvey Thatch Tiles has to be installed in accordance to our presented specifications.
- B) Harvey Roofing Products will only issue a product warrantee subject to installation done by an approved Harvey Roofing installer.
- C) The use of a lightning conductor is not mandatory. However the roof has to be earthed as in the case with any steel (IBR / corrugated) roof.

PRODUCT	SPECIFICATION
Timber truss / support frame / "gum poles"	Micon Coating: Pacsayf™ treated Or similar SABS Approved
Thatch grass layer / Cape Reed	<ul style="list-style-type: none">Remove decayed (top layer)Compact / restore Thatch Treat inside as well as outside with Micon coatings Thatchsayf™ or similar SABS Approved fire retardant.
Pink Aerolite 50 mm or equivalent fire rated insulation	Ensure all ridges, eaves and bottom edges are covered with Pink Aerolite. Do not use as "fill" – Has to cover the battens
Harvey Thatch Tile coated with natural stone on a zinc – aluminium coated substrate of 0.45mm TCT	<ul style="list-style-type: none">not suitable for proximity closer than 1km from breaking surf).
Harvey Thatch Tile coated with natural stone	Galvanised substrate for inland application and zinc-aluminium substrate for coastal application (not suitable for proximity closer than 1km from breaking surf).

Harvey Roofing Products shall not be responsible in any way whatsoever for the actions of incorrect installations and or workmanship.